



ENGINE	
Type, Materials	<ul style="list-style-type: none"> 3.5-Liter V6 Dual Overhead Cam (DOHC) (L → PLTM FWD/AWD Gas) 2.5-Liter L4HV Double Overhead Cam (DOHC) (LE → PLTM FWD/AWD Hybrid)
Valve train	<ul style="list-style-type: none"> 24-Valve D-4S Injection Atkinson Cycle-capable Engine with Dual Variable Valve Timing with Intelligence (Dual VVT-i) and Stop and Start Engine System (L → PLTM FWD/AWD Gas) 16-Valve D-4S Injection Atkinson Cycle Engine with Dual VVT-iE (Variable Valve Timing-Intelligent, intake controlled by electric motor) (LE → PLTM FWD/AWD Hybrid)
Displacement	Gas = 3456cm ³ Hybrid = 2487 cm ³
Bore x Stroke	Gas = 94.0x83.0 (mm) Hybrid = 87.5x103.4 (mm)
Compression Ratio	Gas = 11.8:1 Hybrid = 14:1
Horsepower	<ul style="list-style-type: none"> 295 hp @ 6,600 rpm (L → PLTM FWD/AWD Gas) Combined net hp 243, includes combustion engine with 186 hp @ 6,000 RPM (LE → PLTM FWD/AWD Hybrid)
Engine Torque	<ul style="list-style-type: none"> 263 lb.-ft. @ 4,700 RPM (L → PLTM FWD/AWD Gas) 175 lb.-ft @4400 RPM (LE → PLTM FWD/AWD Hybrid)
Ignition System	Toyota Direct Ignition (TDI)
Fuel System	D-4S
Recommended Fuel	87-octane or higher
Emission Certification	Gas = ULEV 70 Hybrid = SULEV 30
OEM Estimated Fuel Economy* (city/highway/combined MPG)	<ul style="list-style-type: none"> L FWD 21/29/24 L AWD 20/27/23 LE FWD 20/28/23 LE AWD 20/27/23



- LE HV FWD 36/35/36
- LE HV AWD 35/35/35
- XLE → PLTM FWD 21/29/24
- XLE → PLTM AWD 20/27/23
- XLE HV → PLTM HV FWD 36/35/36
- XLE HV → PLTM HV AWD 35/34/35

*EPA-estimated MPG - Actual mileage will vary.

DRIVETRAIN	
Layout	<ul style="list-style-type: none"> • L → PLTM FWD (Gas/HV) = Front-Wheel Drive • L, LE, XLE (Gas AWD) = All-Wheel Drive (AWD) • XSE, LTD, PLTM (Gas AWD) = Dynamic Torque Vectoring AWD • LE → PLTM (HV AWD) = Electronic On-Demand AWD
Transmission Type	<ul style="list-style-type: none"> • L → PLTM (FWD/AWD) = Direct Shift - 8AT, 8-speed Electronically Controlled automatic Transmission • LE → PLTM HV (FWD/AWD) = Electronically controlled Continuously Variable Transmission (ECVT) with sequential shift mode
Gear Ratios (8AT)	1 st - 5.519 2 nd - 3.184 3 rd - 2.050 4 th - 1.491 5 th - 1.234 6 th - 1.000 7 th - .800 8 th - .673 Reverse - 4.220
Front Differential Ratio	Gas = 3.003 Hybrid = N/A

CHASSIS AND BODY	
Suspension	- Front Independent MacPherson strut front suspension with stabilizer bar; trailing-wishbone suspension (XSE uses a



		sport-tuned MacPherson strut front suspension with stabilizer bar)
	- Rear	Multi-link rear suspension with stabilizer bar
Steering	- Type	Electric Power Steering (EPS); power-assisted rack-and-pinion
	- Overall Ratio	14.2
	- Turning Circle Diameter (ft.)	37.4 ft.
	- Turning Circle Radius (ft.)	36.1 ft. 18.7 ft.
Brakes	- Front Type	Power-assisted Ventilated disc
	- Front Diameter	13.3 in.
	- Rear Type	L → PLTM (FWD/AWD) = Solid Disc LE → PLTM HV (FWD/AWD) = Solid Disc with Electronically Controlled Braking (ECB) system and integrated regenerative braking
	- Rear Diameter	13.3 in.
	- Parking	Electronic Parking Brake
Anti-lock Brake System (ABS)		Standard
Wheel Size		<ul style="list-style-type: none"> • L/LE (All) = 18-in. Painted Alloy • XLE (All) = 18-in. Machined Alloy • XSE (All) = 20-in, Machined Alloy • LTD (All) = 20-in. Alloy • PLTM (All) = 20-in. Painted Alloy
Wheel Type and Material		Standard aluminum alloy
Tire Size		<ul style="list-style-type: none"> • L → XLE (All) = P235/65R18 • XSE → PLTM (All) = P235/55R20
Spare Tire/Wheel		<ul style="list-style-type: none"> • Temporary



EXTERIOR DIMENSIONS	
Wheelbase	112.2 in.
Overall Length	194.9 in. (XSE = 197.4)
Overall Width	76.0 in.
Unload Height (no antenna)	68.1 in.
Track - Front/Rear	65.3/65.4
Ground Clearance	8.0 in.
Approach/Departure Angle	FWD Gas = 18.1 / 23 AWD Gas = 17.9 / 23 FWD/AWD Hybrid = 18.1 / 22.7 FWD/AWD XSE = 16.9/21.1

INTERIOR DIMENSIONS	
Seating Capacity (standard/optional)	<ul style="list-style-type: none"> • L (All) = 8 • LE (All) = 8 • XLE (All) = 7/8 • XSE = 7 • LTD (All) = 7/8 • PLTM (All) = 7
Headroom	
- Front	<ul style="list-style-type: none"> • 39.9 in. (w/o moonroof) • 38.4 (w/moonroof) • 38.4 (w/panoramic)
- Second Row	<ul style="list-style-type: none"> • 39.4 in. (w/o moonroof) • 39.4 in. (w/ moonroof) • 37.1 in. (w/panoramic)
- Third Row	<ul style="list-style-type: none"> • 36.1 in (ALL)
Legroom	
- First/Second/Third (in.)	40.4/41.0/27.7
Shoulder Room	
- First	<ul style="list-style-type: none"> • 59.0 in. (w/o shade)



#ToyotaHighlander

- Second Row	<ul style="list-style-type: none"> • 59.0 in. (with shade) • 58.7 in. (w/o shade)
- Third Row	<ul style="list-style-type: none"> • 58.4 in. (with shade) • 55.0 in. (w/o shade) • 55.0 in. (with shade)
Hip Room	
- First/Second/Third (in.)	57.2/57.0/45.6
Cargo Volume	
- Behind front	84.3 cu. ft.
- Behind second row	48.4 cu. ft.
- Behind third row	16 cu. ft.
Passenger Volume	
	<ul style="list-style-type: none"> • 141.3 (w/o moonroof) • 139.1 (w/ moonroof) • 136.1 (w/ panoramic)
EPA Class	Midsize SUV

WEIGHTS AND CAPACITIES

Curb Weight (FWD/AWD)	<ul style="list-style-type: none"> • L 4,145/4,330 • LE 4,145/4,330 • LE HV 4,330/4,465 • XLE 4,195/4,370 • XLE HV 4,365/4,515 • XSE 4,205/4,400 • LTD 4,260/4,450 • LTD HV 4,430/4,595 • PLTM 4,260/4,450 • PLTM HV 4,430/4,595
Payload (FWD/AWD)	<ul style="list-style-type: none"> • L 1,685/1,605 • LE 1,685/1,605 • LE HV 1,495/1,535 • XLE 1,635/1,565 • XLE HV 1,595/1,485 • XSE 1,625/1,535 • LTD 1,570/1,485 • LTD HV 1,530/1,405



#ToyotaHighlander

	<ul style="list-style-type: none"> • PLTM 1,570/1,485 • PLTM HV 1,530/1,405
GVWR (lb.)	L → PLTM (FWD Gas) = 5,830 L → PLTM (AWD Gas) = 5,935 LE → PLTM (FWD HV) = 5,960 LE → PLTM (AWD HV) = 6,000
Max Towing Capacity	5,000 lbs. (FWD/AWD Gas) 3,500 lbs. (FWD/AWD HV)
Fuel Capacity (gal.)	17.9 (FWD/AWD Gas) 17.1 (FWD/AWD Hybrid)
Hybrid Engine Oil	Fully Variable Oil Pump
Hybrid Cooling System	Variable Cooling System

###